

AQUA MIX® ENRICH 'N' SEAL™

1. Product Name

Aqua Mix® Enrich 'N' Seal™

2. Manufacturer

Custom Building Products
13001 Seal Beach Blvd.
Seal Beach, CA 90740-2757
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

Aqua Mix Enrich 'N' Seal™ is a premium, no-sheen, enhanced-look 100% polymer-solid, penetrating sealer formulated to darken, enrich, and highlight the character and beauty of unsealed natural stone.

KEY FEATURES

- Rejuvenates the color and improves the appearance of worn and weathered stone
- May also be used as a pre-grouting sealer
- Allows moisture-vapor transmission
- Effectively seals and darkens the color of grout joints

AREAS OF USE

- Unsealed natural stone such as marble, granite, slate, limestone, travertine, quartzite, and sandstone
- Effective for interior and exterior applications

LIMITATIONS

- Do not allow sealer to come in contact with any non-recommended surface as product is not completely removable
- Sealers and finishes should not be used before or after use of Enrich 'N' Seal™
- If Enrich 'N' Seal™ is not wiped completely dry within 5 minutes, a grey residue may form. If residue occurs, use a scrub brush or floor machine with Aqua Mix NanoScrub® to remove sealer residue. Always try a small test area to ensure results. If results are not satisfactory, contact Technical Services for additional options
- Keep floor surfaces dry and clean to reduce possibility of slip-fall accidents. Routine pressure-washing will affect expected wear
- Sealers will not prevent surface wear or etching from acids or caustic chemicals

EXPECTED WEAR UP TO 15 YEARS

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Exterior applications may require more frequent reapplications
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear



4. Technical Data

TEST METHOD	TEST RESULTS
Stain Resistance (CTI 72)	Excellent
Service Time	12 hours
Full Cure	48 hours

5. Installation

METHODS

Application

Read entire label before using. For new installations, sealer can be applied to a dry surface as soon as 72 hours after grouting. Surface must be clean, dry, and free of existing sealers or coatings. Apply using a sponge, brush, paint pad, cotton towel, or sprayer. NOTE: Avoid overlapping and rundown. On vertical surfaces, apply bottom to up or apply to each tile prior to installation. Be sure any sealer that does not penetrate surface is polished dry off surface within 5 minutes of each application using absorbent paper or cotton towels. If Enrich 'N' Seal residue is not completely removed from stone and grout surface within 5 minutes of application, a grey residue may form. If non-polished surfaces are left shiny after application, surfaces must be wiped dry as this indicates surface residue remains. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between applications. Remove surface residue after each application. Ready for surface traffic in 12 hours after final application. Keep dry for 12 hours. Achieves full cure in 48 hours. Some highly porous surfaces may require an additional application after full cure insuring that all residue is removed within 5 minutes. Clean applicator tools with mineral spirits after each use.

Pre-Grouting Application

Apply over clean stone or tile a minimum of 24 hours prior to grouting - follow application procedures above.



Coverage
 Approximately 500 to 1,500 sq. ft. (46 m² to 139 m²) per coat per gallon (3.8 L), depending on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

Handling and Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 40° F and 90° F (4° C and 32° C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements

DANGER

FLAMMABLE. MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Keep away from heat and sources of ignition. Wear skin and eye protection. Do not breathe vapor or spray. Contains alkylalkoxysilanes. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

6. Availability & Cost

Contact the manufacturer or visit custombuildingproducts.com for information about product cost and availability.

	ITEM CODE	SIZE	PACKAGE
USA	100250	1 pt (473 ml)	Bottle
USA	100251-4	1 qt (946 ml)	Bottle
USA	100252	1 gallon (3.8 L)	Bottle
Canada	C100250	1 pt (473 ml)	Bottle
Canada	C100251-4	1 qt (946 ml)	Bottle
Canada	C100252	1 gallon (3.8 L)	Bottle

7. Limited Product Warranty

Custom Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom’s sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom’s printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

For details and complete warranty information, visit custombuildingproducts.com

8. Maintenance

Aqua Mix Concentrated Stone & Tile Cleaner or AquaKleen™ or AquaShield™ is recommended for routine spray and wipe cleaning and resealing.

9. Technical Services

For technical assistance contact Custom Building Products or visit custombuildingproducts.com.

10. Filing Systems

Additional product information is available from the manufacturer upon request.

Related Products:

- Aqua Mix®
- AquaKleen™
- Concentrated Stone & Tile Cleaner

